



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

B01J 19/18

A2

(11) International Publication Number:

WO 00/48730

(43) International Publication Date:

24 August 2000 (24.08.00)

(21) International Application Number: PCT/GB00/00523

(22) International Filing Date: 17 February 2000 (17.02.00)

(30) Priority Data:

9903474.6

17 February 1999 (17.02.99)

GB

(71) Applicant (for all designated States except US): UNIVERSITY OF NEWCASTLE [GB/GB]; 6 Kensington Terrace, Newcastle upon Tyne NE1 7RU (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): RAMSHAW, Colin [GB/GB]; 20 High View, Ponteland, Newcastle upon Tyne NE20 9ET (GB); JACHUCK, Roshan, Jeet, Jee [IN/GB]; Abbey Farm, 10 Marcross Close, North Walbottle, Newcastle upon Tyne NE1 7RU (GB).


(74) Agent: HARRISON GODDARD FOOTE; Tower House, Merriion Way, Leeds LS2 8PA (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

Without international search report and to be republished upon receipt of that report.

(54) Title: ROTATING SURFACE OF REVOLUTION REACTOR WITH SHEARING MECHANISMS



(57) Abstract

A reactor including a rotatable disc (3) having a surface (5) onto which reactant (15) is supplied by way of a feed (4). The disc (3) is rotated at high speed, and the reactant (15) spills over the surface (5) so as to form a film (17). A shear member (18, 20) is mounted close to the surface (5) so as to contact the film (17) during operation of the reactor, thereby applying a shearing force to the reactant (15) so as to aid mixing.